

NFC Epoxy Tag



Quick Details

Leadercolor LDF-4530E RFID Tag is produced with PVC and epoxy material, it can OEM with customized design, each RFID chip has a unique ID code, in which high frequency and ultra high frequency chips can also be written according to customer needs. Based on the characteristics of RFID, which is widely used for school, bank, super market etc. Management.

Description

RFID Parameter	
Model No.	LDF-4530E
Type	RFID Epoxy Tag
Protocol	ISO / IEC 14443 A
Frequency	Worldwide HF 13.56Mhz
Chip	Compatible MIFARE Classic® 1K
Memory	UID 4/7Byte
	User 1K Byte
Read&Write	Supported
Read Range	0.1-10cm
Data retention	10years
Programming Cycles	100,000 cycles
Physical Parameter	
Size	45*30mm
Antenna Material	Aluminum Etching
Surface Material	PVC and Epoxy
Encode	Supported

Installation	Self adhesive
Operating temperature	1>Recommended: -25°C to +60°C 2>Operating Temp: -20°C to +80°C
Package	Single pack
Customized	Chips / Printing / Color / Size / Material

Application

- ✓ NFC posters, NFC device data connection and data transmission
- ✓ Mobile payment, Mobile wallet
- ✓ Product identification, personnel identification management
- ✓ E-ticketing, Loyalty System, Marketing and Advertisements