

Hologram NFC Epoxy Tag



Quick Details

Leadercolor LDF-D30E RFID Tag is produced with Solid color background with shiny logo and shiny Sparkling hologram background, it can OEM with customzied design, each RFID chip has a unique ID code, in which high frequency and ultra high frequency chips can also be written according to customer needs. Based on the characteristics of RFID, which is widely used for school, bank, super market etc. Mangement.

Description

RFID Parameter	
Model No.	LDF-D30E
Type	HF RFID Epoxy Tag
Protocol	ISO / IEC 14443 A
Frequency	Worldwide HF 13.56Mhz
Chip	Compatible MIFARE Classic® 1K
Memory	UID 4/7Byte
	User 1K Byte
Read&Write	Supported
Read Range	0.1-10cm
Data retention	10years
Programming Cycles	100,000 cycles
Physical Parameter	
Size	Dia30mm
Material	PVC and Epoxy+shiny hologram

Antenna Material	Aluminum Etching
Encode	Supported
Installation	Single or Self adhesive
Operating temperature	1>Recommended: -25°C to +60°C 2> Operating Temp: -20°C to +80°C
Package	Single pack
Customized	Chip / Antenna / Material / Glue / Printing / Craft

Application

- ✓ NFC posters,NFC device data connection and data transmission
- ✓ Mobile payment, Mobile wallet
- ✓ Product identification, personnel identification management
- ✓ E-ticketing, Loyalty System, Marketing and Advertisements